

TrackFlex Carrier Vehicle Requirements

Name:	
Address:	
Company:	
Phone:	
Email:	

Type of Carrier Vehicle	
Brand and Model	

Tractor	Unladen weight greater than 3500 kg for 3.0m - 5.0m TrackFlex
	Unladen weight greater than 4500 kg for 4.5m - 7.5m TrackFlex
	Crawlers gears to maintain cleaning speed of approx 1.5kph


Skid Steer	Needs unladen weight greater than 5000 kg for 3.0m - 5.0m TrackFlex
Excavator	

Hydraulics Requirements

Hydraulic forward: min 37 l/m, max 60 l/m, with approximately 3000 psi (hydraulic performance)

Hydraulic return: A dedicated free flow return directly into the tank is required. Continuous flow is required to operate the SunBrush

A hydraulic pressure detent is also required for brush operation



	<p>Standard Quick Fit Coupling</p>
	<p>Size: _____</p>
	<p>Flat Face Coupling</p>
	<p>Size: _____</p>

Mounting Linkage Requirements



Front 3 Point Linkage - Category 2

32" (820mm) Between Link Arms

Recommended Front Linkage Suppliers:

- Zuidberg
- Le Forge
- Sauter

Extra hydraulic service will be required to lift and lower the link arms for mounting / dismounting the SunBrush from the tractor.

Electrical Requirements in Cab



1 x 12V, 25 Ampere 3 Pin plug for joystick control box.

The machine is supplied with suction cups to mount the joystick to the carrier vehicle.

