

# Paint Removal Agent

## Technical Datasheet

### Description

**Paint Removal Agent (PRA)** is a cleaning product specifically developed for the removal of paint residues from glass surfaces of solar panels. The formula of this solution is designed to be as mild as possible with the solar panels, so that it is easy to use and does not present any health risks for professionals.

### Dilution specifications

#### **Adjust the product dilution according to the problem**

If your modules are contaminated with water-based spray paint, use a dilution of 1:5 (1kg PRA to 5 liters of water);

If your modules are contaminated with one of the following: exterior coatings, interior paints, wood coatings, multi-surface enamels, use a dilution of 1:2 (1kg PRA for 2 liters of water)

### Applications

Removal of interior paints, exterior coatings, multi-surface enamels, and water-based spray paints from the surface of solar module glass.

### Instructions of use

1. **Dilute** the Paint Removal Agent concentrate with the correct amount of water (see dilution ratio above);
2. **Apply** the diluted solution directly on the affected areas, making sure that the surface is fully covered;
3. **Leave** the product to act for 10 to 15 minutes;
4. **Brush** the entire area to remove the paint residue. If necessary, repeat steps 2 to 4 until all residues are properly removed;
5. **Rinse** the module thoroughly with water, making sure that all excess product is removed.

## Comments

Please follow the instructions on the safety data sheet for safe handling of the product.

## Properties

**Appearance:** Colorless transparent liquid;

**Odor:** Characteristic;

**Solubility in water:** Fully miscible in water.

## Packaging

Transparent Drums of 5 and 20 kg, and IBC of 1000 kg.